

TRYLON SuperTITAN™ GUYED TOWERS

Tower Height (Feet)	TESSCO Part No.	List Price	Allowable Antenna Area in ft² at 70/90/110 winds*			
			No Ice Round	No Ice Flat	1/2" Ice Round	1/2" Ice Flat
100	415789	\$4,545.00	75/48/31	45/28/18	64/30/18	38/18/11
120	426757	5,175.00	65/46/30	39/27/18	58/22/7	35/13/4
150	496768	6,584.00	58/43/26.5	34/25/15	49/15/—	29/9/—
160	422778	6,905.00	56/42/25	33/25/15	47/13/—	28/8/—
170	481790	7,266.00	54/41/24	32/24/14	44/11/—	26/7/—
180	490780	7,548.00	52/40/23	31/24/13	41/9/—	25/5/—
200	411760	8,758.00	49/38/21	29/22/12	36/5/—	22/3/—
220	488759	9,434.00	47/37/19	28/22/12	36/5/—	22/3/—
250	420785	10,408.00	44/34.5/15	26/20/9	22/—/—	13/—/—
300	453781	12,778.00	39/30/14	23/16/3	8/—/—	5/—/—
350	436799	15,900.00	34/22/—	20/13/—	—/—/—	—/—/—

* Allowable antenna area for antennas at 70/90/110 wind speeds designed in accordance with ANSI/EIA 222 standard and based on loads being centrally located and balanced over the tower top. (— indicates tower failure)

The SuperTITAN guyed tower line is an extremely robust, one-size-fits-all tower from Tylon. SuperTITAN guyed towers can be guyed up to 480 feet, bracketed up to 100 feet or free-standing up to 70 feet, offering numerous solutions for varying tower needs. Each 10 section is made with solid steel tubing side rails and electrically welded continuous 1/2" steel rod S-bracing. The external splice spigots are easy to align and use 5/8" x 6" A325 splice bolts that just drop in, making installation easier and faster. SuperTITAN guyed tower kits come with all the necessary material for proper installation, including guy anchor rods, anchor rod grounding kits, guy wire and hardware and a star base. Recommended accessories include a tower grounding kit, a cable safety climb kit and anti-climb shield kit. For information on additional heights, please call 1-800-472-7373.

